



1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Thermoset Rubber Wall Base. Made in USA.
- 1.2. **Manufacturer:**
Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkett.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett BaseWorks™ Thermoset Rubber Wall Base is manufactured from a proprietary rubber formulation designed specifically to meet the performance and dimensional requirements of ASTM F-1861, Type TS, Group 1 (solid), Style A and B, Standard Specification for Resilient Wall Base.

1.3.2. Styles & Physical Characteristics:

| Style | TSB-XX with toe (Coved) | TSBT-XX toeless (Straight) |
|------------------------------|--|--|
| Thickness | 0.125" | 0.125" |
| Sizes Available | 2 1/2" 3" 3 1/2" 4" 4 1/2" 6" | 2 1/2" 3" 3 1/2" 4" 4 1/2" 6" |
| Lengths | 4' straight lengths 120' coiled (100' for 6") | 4' straight lengths 120' coiled (100' for 6") |
| Factory-Made Inside Corners | 4" returns Packaged 25 to a carton Product Code: LIC | 4" returns Packaged 25 to a carton Product Code: LIC |
| Factory-Made Outside Corners | 4" returns Packaged 25 to a carton Product Code: LOC | 4" returns Packaged 25 to a carton Product Code: LOC |

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets or exceeds the performance requirements for resistance to heat/light aging, chemicals, and dimensional stability when tested to the methods, as described, in **ASTM F1861**.
- 2.2. **Flexibility:** ASTM F137 - Will not crack, break, or show any signs of fatigue when bent around a 1/4" (6.4 mm) diameter cylinder.
- 2.3. **Resistance to Light:** ASTM F1515 – Passes ΔE ≤ 8.0
- 2.4. **Fire Resistance** (ASTM E648/NFPA 253) Critical Radiant Flux: Class 1 (Minimum 0.45 W/cm²)
- 2.5. **Chemical Resistance (ASTM F925):** Passed
- 2.6. **CAN/ULC-S102.2-18:** FSR 145 / SDV 285

3. INSTALLATION

- 3.1. See Tarkett BaseWorks wall base installation instructions for complete details.
- 3.2. **Adhesives:**
 - **Tarkett 960 Cove Base Adhesive** (Porous surfaces):
Application: 1/8" x 1/8" x 1/8" square notched trowel
Approximate coverage per gallon:
2.5" = 300-350 lf.
3" = 275-325 lf.
3.5" = 230-280 lf.
4" = 200-250 lf.
4.5" = 175-225 lf.
6" = 100-150 lf.

- **Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)

Application: Brush or roller

Approximate coverage:

| Base Size | Quart | Gallon |
|-----------|-----------|-------------|
| 2.5" | 57-86 lf. | 345-516 lf. |
| 3" | 48-72 lf. | 288-430 lf. |
| 3.5" | 41-61 lf. | 246-368 lf. |
| 4" | 36-54 lf. | 216-322 lf. |
| 4.5" | 32-48 lf. | 192-286 lf. |
| 6" | 24-36 lf. | 144-215 lf. |

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett BaseWorks Wall Base Installation & Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com
 Contact Technical support at (800)-899-8916 or Email: Resilient.TechnicalSupport@Tarkett.com
Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 2-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
 30000 Aurora Road
 Solon, Ohio 44139
 800.899.8916 Ext. 9297 Fax 440.632.5643
 info@tarkettna.com

www.tarkett.com